



**2024
TOOLS**

www.ecko.co.nz

HAMMAHAND® Weatherboard Nailer WB75



HAMMAHAND® XNOSE® Hole Locator Attachment for Weatherboard Nailer



Endorsed by James Hardie for Linea® Weatherboard
Save up to 80% in time and labour
Accurate hole locator
User friendly
Fastener dia. : up to 5mm wide

HAMMAHAND® COMBO KIT Weatherboard Nailer Combo Kit WB75KIT

Includes
Weatherboard nailer x 1
V8compressor x 1
Light weight air hose 15M x 1



**ONE
FOR ALL**

**2
YEAR
WARRANTY**

■ Features

Save up to 80% in time and labour
Covers a wide range of manual applications
Accepts both wire welded and WirelessCoil nails without adjustment
Light weight, magnesium body, tough nail magazine cover
Recommended 10 drops daily. Disconnect the air hose,
apply 10 drops of pneumatic oil into the nailer.

■ Specifications

Dimensions (mm)	L313 x W132 x H316
Weight	3.10 kg
Operating pressure	70 - 120 psi
Magazine capacity	225 - 300 nails
Fasteners diameter	2,50 - 3,33mm
Fasteners length	27 - 75mm

■ Applications

Most James Hardie Building Products
Weatherboard
Tile & Slate underlay
HomeRAB
Ply bracing
Soffit lining
Cavity batten
HardieFlex
RAB Board

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for HAMMAHAND® coil nails

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
HAMMAHAND® Weatherboard Systems			
EC-WB75	ECKO HAMMAHAND® Weatherboard Nailer (27 - 75mm)	Each	9421023348923
EC-WB75KIT	ECKO HAMMAHAND® Weatherboard Nailer Combo Kit (1 x WB75, 1 x EK1501, 1 x Air Hose)	Each	9421023349043
EC-P90	ECKO HAMMAHAND® Airpunch® Air Punch	Each	9421023348299
EC-Xnose	ECKO HAMMAHAND® XNOSE® Hole Locator Attachment For Weatherboard Nailer	Each	9421023348329
EC-EK1501	ECKO HAMMAHAND® V8compressor® Construction Air Compressor	Each	9421023348169
H0805S	ECKO Light Weight Air Hose - 15M	Each	9421023348183
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

HAMMAHAND® Airpunch® P90



2
YEAR
WARRANTY

■ Features

Endorsed by James Hardie for Linea Weatherboard
Save up to 80% in time and labour
Consistent punching result
Light weight, magnesium body
Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Applications

Nail punch
Timber recycling

■ Specifications

Dimensions (mm)	L242 x W56 x H235
Weight	0.8 kg
Operating pressure	50 - 100 psi
Magazine capacity	N/A
Fasteners diameter	5.0mm
Fasteners length	50 - 90mm

HAMMAHAND® V8compressor® Construction Air Compressor EK1501



1
YEAR
WARRANTY

■ Features

Light weight, easy carry
Quick recovery
Stable inside the vehicle
Ultra-low voltage start

■ Air Hose

Light weight
15 meters
Product code: H0805S



■ Specifications

Horse power	1.5HP peak
Weight	18 kg
Pump type	Oil-less
SCFM@90psi	2.30
Pump-up time	35 seconds
Recovery time	10 seconds

HAMMAHAND® High Wind Zone Weatherboard Nailer WB90



■ Features

Endorsed by James Hardie for high wind zone cladding
Save up to 80% in time and labour
Light weight, magnesium body
Tough nail magazine cover
Belt hook
Depth adjustment for precision nailing

■ Specifications

Dimensions (mm)	L313 x W132 x H316
Weight	3.65 kg
Operating pressure	80 - 120 psi
Magazine capacity	150 - 300 nails
Fastener diameter	3.15 - 3.33mm
Fastener length	75 - 90mm

■ Applications

High wind zone cladding
Cavity battens
RAB Board

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for HAMMAHAND® coil nails

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
HAMMAHAND® High Wind Zone Weatherboard Systems			
EC-WB90	ECKO HAMMAHAND® High Wind Zone Weatherboard Nailer (50 - 90mm)	Each	9421023348909
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

Joist Hanger Nailer PN38



■ Features

One handed joist nailing
Easy to locate connector holes
Powerful - Will nail through the toughest timber surfaces
User friendly
Safe nailing process
No wastage of product nails

■ Specifications

Dimensions (mm)	L292 x W124 x H237
Weight	1.8 kg
Operating pressure	100 - 120 psi
Magazine capacity	24 nails
Fastener diameter	3.33mm
Fastener length	38mm

■ Applications

Joist hanger and product nail installation
Sub-floor strip brace to framing
Strap brace and multibrace installation
Nail on plate installation

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for joist hanger nails

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Joist Hanger Nailer			
EC-PN38	ECKO Joist Hanger Nailer	Each	9421023340125
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

FrameTec100 Construction Air Framer ND100S



■ Features

Accepts both D head & Round head paper collated 34° framing nails
Anti-dry firing mechanism
Easy jam clearing
Aggressive nose design for skew nailing
No-Mark pad

■ Specifications

Driving power	1296.96 inch/lbs @120psi
Dimensions (mm)	L428 x W138 x H363
Weight	3.44 kg
Operating pressure	100 - 120 psi
Magazine capacity	90 nails
Fastener diameter	2.87 - 3.15mm
Fastener length	50 - 100mm

■ Applications

Framing	J frame
Trusses	Decking
Subflooring	Fencing

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for paper collated framing nails

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Construction Air Framer			
EC-ND100S	ECKO FrameTec100 Construction Air Framer (Rear-loading)	Each	9421023348886
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

FrameTec90™ Construction Air Framer ND90S



■ Features

Accepts both D head & Round head paper collated 34° framing nails
Anti-dry firing mechanism
Easy jam clearing
Aggressive nose design for skew nailing
No-Mark pad

■ Specifications

Driving power 1099.32 inch/lbs
Dimensions (mm) L448 x W151 x H336
Weight 3.55 kg
Operating pressure 100 - 120 psi
Magazine capacity 90 nails
Fastener diameter 2.87 - 3.15mm
Fastener length 50 - 90mm

■ Applications

Framing J frame
Trusses Decking
Subflooring Fencing

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for paper collated framing nails

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Construction Air Framer			
EC-ND90S	ECKO FrameTec90™ Construction Air Framer	Each	9421023348374
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

ExteriorMaster 15 Gauge Air Angle Bradder AB1550FN



■ Features

Light weight
Magnesium body for job site durability
Adjustable depth control
No-Mark pad

■ Specifications

Dimensions (mm)	L276 x W68 x H261
Weight	1.40 kg
Operating pressure	70 - 120 psi
Magazine capacity	86 brads
Fastener diameter	1.90 - 1.60mm
Fastener length	25 - 50mm

■ Applications

Exterior & Interior trim	Light framing
Door & Window construction	Cabinet work
Decoration	Interior finishing

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for 15 gauge FN angle brads

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Air Angle Bradder			
EC-AB1550FN	ECKO ExteriorMaster® 15 Gauge Air Angle Bradder	Each	9421023348305
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

16 Gauge Air Straight Bradder BC65



■ Features

Depth control adjustment
High capacity rear loading magazine
Rubber grip provide comfortable feel

■ Specifications

Dimensions (mm)	L287 x W73 x H278
Weight	1.76 kg
Operating pressure	100 - 120 psi
Magazine capacity	100 brads
Fastener diameter	1.60mm
Fastener length	25 - 63mm

■ Applications

Decoration	Boards in furniture
Light frame	Hardwood flooring
Door & Window	

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for 16 gauge straight brads

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Air Angle Bradder			
EC-BC65	ECKO 16 Gauge Air Straight Bradder	Each	9421023348688
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

Wrap-Tacker® Air Stapler RD1116P



■ Applications

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

■ Specifications

Dimensions (mm) L220 x W140 x H45
Weight 1 kg
Operating pressure 70 - 100 psi
Magazine capacity 100 staples
Fastener length 6 - 14mm

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for 140/A11 series staples

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Construction Stapler			
EC-RD1116P	ECKO Wrap-Tacker® Air Stapler	Each	9421023348350
EC-XPRO	ECKO Construction Hammer Tacker (6 - 14mm)	Each	9421023349029
EC-LT1	ECKO H/D Staple Gun Tacker (6 - 14mm)	Each	9421023348213
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

Construction Hammer Tacker XPRO



■ Applications

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

■ Specifications

Dimensions (mm)	L310 x W30 x H75
Weight	1.06 kg
Fasteners length	6 - 14mm

■ Fasteners

Check our fasteners catalogue for 140/A11 series staples

H/D Staple Gun Tacker LT1



■ Applications

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

■ Specifications

Dimensions (mm)	L250 x W30 x H150
Weight	1.07 kg
Fasteners length	6 - 14mm

■ Fasteners

Check our fasteners catalogue for 140/A11 series staples

Palm Nailer PNC1



■ Features

Perfect for timber framing in construction site
Ideal for driving loose nails in confined area & for nailing of metal connectors & joist hangers
Easier & Simple to use

■ Specifications

Dimensions (mm)	L132 x W82 x H124
Weight	1.18 kg
Operating pressure	100 - 120 psi
Magazine capacity	1 nail
Fastener diameter	2.87 - 4.10mm (standard nose) 4.88 - 7.94mm (large nose) - optional
Fastener length	32 - 178mm

■ Applications

Retaining wall

■ Maintenance

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

■ Fasteners

Check our fasteners catalogue for loose nails series

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Palm Nailer			
EC-PNC1	ECKO Palm Nailer	Each	9421023348022
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each	9421023348862

RebarMaster Cordless Rebar Tool XPOWERPLUS



■ Features

Save up to 80% in time & labour
No more RSI
One handed operation
Consistent fixing performance
Brushless twisting motor

■ Specifications

Dimensions (mm) L297 x W109 x H300
Weight (incl. battery) 2.60 kg
Time per tie 0.7 second
Wraps per tie 2 or 3 wraps
Rebar size 12 - 40mm
Ties per coil Approx. 160 ties
Ties per charge Over 5,000 ties / 2 wraps
Over 4,500 ties / 3 wraps
Charging time 90 minutes

■ Applications

Foundations
Floor heating
Commercial buildings
Road & Bridge
Precast plants

■ Fasteners

Check our fasteners catalogue for rebar wire

PRODUCT CODE	DESCRIPTION	PER	GS1 BARCODE
Cordless Rebar Tool			
EC-XPOWERPLUS	ECKO RebarMaster Cordless Rebar Tool (Li-ion Battery)	Each	9421023349067



TECHNICAL SUPPORT

info@ecko.co.nz
(09) 279-0210
www.ecko.co.nz



@eckofasteners

