



makes your job easier

TOOLS

PRODUCT CATALOGUE

HAMMAHAND® Weatherboard Nailer WB75

HAMMAHAND®
Weatherboard Nailing Solution



HAMMAHAND® XNOSE® Hole Locator Attachment for Weatherboard Nailer



Endorsed by James Hardie for Linea® Weatherboard
Save up to 80% in time and labour
Accurate hole locator
User friendly
Fastener dia.: up to 5mm wide

HAMMAHAND® COMBO KIT Weatherboard Nailer Combo Kit WB75KIT

Includes
Weatherboard nailer x 1
V8compressor x 1
Light weight air hose 15M x 1



**ONE
FOR ALL**

**2
YEAR
WARRANTY**

FEATURES

Save up to 80% in time and labour.
Covers a wide range of manual applications.
Accepts both wire welded and WirelessCoil nails without adjustment.
Light weight, magnesium body, tough nail magazine cover.
Recommended 10 drops daily. Disconnect the air hose,
apply 10 drops of pneumatic oil into the nailer.

SPECIFICATIONS

Dimensions (mm)	L313 x W132 x H316
Weight	3.10 kg
Operating pressure	70 - 120 psi
Magazine capacity	225 - 300 nails
Fasteners diameter	2.50 - 3.33mm
Fasteners length	27 - 75mm

APPLICATIONS

Most James Hardie Building Products
Weatherboard
Tile & Slate underlay HomeRAB
Ply bracing Soffit lining
Cavity batten HardieFlex
RAB Board

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for HAMMAHAND® coil nails.

Product Code	Description	QTY
EC-WB75	ECKO HAMMAHAND® Weatherboard Nailer (27 - 75mm)	Each
EC-WB75KIT	ECKO HAMMAHAND® Weatherboard Nailer Combo Kit (1 x WB75, 1 x EK1501, 1 x Air Hose)	Each
EC-P90	ECKO HAMMAHAND® Airpunch® Air Punch	Each
EC-Xnose	ECKO HAMMAHAND® XNOSE® Hole Locator Attachment For Weatherboard Nailer	Each
EC-EK1501	ECKO HAMMAHAND® V8compressor® Construction Air Compressor	Each
H0805S	ECKO Light Weight Air Hose - 15M	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

HAMMAHAND® Airpunch® P90

HAMMAHAND®
Weatherboard Nailing Solution



2
YEAR
WARRANTY

FEATURES

Endorsed by James Hardie for Linea Weatherboard.
Save up to 80% in time and labour.
Consistent punching result.
Light weight, magnesium body.
Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

APPLICATIONS

Nail punch
Timber recycling

SPECIFICATIONS

Dimensions (mm)	L242 x W56 x H235
Weight	0.8 kg
Operating pressure	50 - 100 psi
Magazine capacity	N/A
Fasteners diameter	5.0mm
Fasteners length	50 - 90mm

HAMMAHAND® V8compressor® Construction Air Compressor EK1501

HAMMAHAND®
Weatherboard Nailing Solution



1
YEAR
WARRANTY

FEATURES

Light weight, easy carry.
Quick recovery.
Stable inside the vehicle.
Ultra-low voltage start.

AIR HOSE

Light weight
15 meters
Product code: H0805S



SPECIFICATIONS

Horse power	1.5HP peak
Weight	18 kg
Pump type	Oil-less
SCFM@90psi	2.30
Pump-up time	35 seconds
Recovery time	10 seconds

HAMMAHAND® High Wind Zone Weatherboard Nailer WB90

HAMMAHAND®
Weatherboard Nailing Solution



FEATURES

Endorsed by James Hardie for high wind zone cladding.
Save up to 80% in time and labour.
Light weight, magnesium body.
Tough nail magazine cover.
Belt hook.
Depth adjustment for precision nailing.

SPECIFICATIONS

Dimensions (mm)	L313 x W132 x H316
Weight	3.65 kg
Operating pressure	80 - 120 psi
Magazine capacity	150 - 300 nails
Fastener diameter	3,15 - 3,33mm
Fastener length	75 - 90mm

APPLICATIONS

High wind zone cladding
Cavity battens
RAB Board

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for HAMMAHAND® coil nails.

Product Code	Description	QTY
EC-WB90	ECKO HAMMAHAND® High Wind Zone Weatherboard Nailer (50 - 90mm)	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

Joist Hanger Nailer PN38



FEATURES

- One handed joist nailing.
- Easy to locate connector holes.
- Powerful - Will nail through the toughest timber surfaces.
- User friendly.
- Safe nailing process.
- No wastage of product nails.

SPECIFICATIONS

Dimensions (mm)	L292 x W124 x H237
Weight	1.8 kg
Operating pressure	100 - 120 psi
Magazine capacity	24 nails
Fastener diameter	3,33mm
Fastener length	38mm

APPLICATIONS

- Joist hanger and product nail installation.
- Sub-floor strip brace to framing.
- Strap brace and multibrace installation.
- Nail on plate installation.

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for HAMMAHAND® coil nails.

Product Code	Description	QTY
EC-PN38	ECKO Joist Hanger Nailer	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

FrameTec100 Construction Air Framer ND100S



FEATURES

Accepts both D head & Round head paper collated 34° framing .
 Anti-dry firing mechanism.
 Easy jam clearing.
 Aggressive nose design for skew nailing.
 No-Mark pad.

SPECIFICATIONS

Driving power	1296.96 inch/lbs @120psi
Dimensions (mm)	L428 x W138 x H363
Weight	3.44 kg
Operating pressure	100 - 120 psi
Magazine capacity	90 nails
Fastener diameter	2.87 - 3.15mm
Fastener length	50 - 100mm

APPLICATIONS

Framing	J frame
Trusses	Decking
Subflooring	Fencing

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for paper collated framing nails.

Product Code	Description	QTY
EC-ND100S	ECKO FrameTec100 Construction Air Framer (Rear-loading)	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

FrameTec90™ Construction Air Framer ND90S



FEATURES

Accepts both D head & Round head paper collated 34° framing .
 Anti-dry firing mechanism.
 Easy jam clearing.
 Aggressive nose design for skew nailing.
 No-Mark pad.

SPECIFICATIONS

Driving power	1099,32 inch/lbs
Dimensions (mm)	L448 x W151 x H336
Weight	3,55 kg
Operating pressure	100 - 120 psi
Magazine capacity	90 nails
Fastener diameter	2,87 - 3,15mm
Fastener length	50 - 90mm

APPLICATIONS

Framing	J frame
Trusses	Decking
Subflooring	Fencing

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for paper collated framing nails.

Product Code	Description	QTY
EC-ND90S	ECKO FrameTec90™ Construction Air Framer	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

ExteriorMaster 15 Gauge Air Angle Bradder AB1550FN



FEATURES

Light weight.
Magnesium body for job site durability.
Adjustable depth control.
No-Mark pad.

SPECIFICATIONS

Dimensions (mm)	L276 x W68 x H261
Weight	1.40 kg
Operating pressure	70 - 120 psi
Magazine capacity	86 brads
Fastener diameter	1.90 - 1.60mm
Fastener length	25 - 50mm

APPLICATIONS

Exterior & Interior trim	Light framing
Door & Window construction	Cabinet work
Decoration	Interior finishing

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for 15 gauge FN angle brads.

Product Code	Description	QTY
EC-AB1550FN	ECKO ExteriorMaster® 15 Gauge Air Angle Bradder	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

16 Gauge Air Straight Bradder BC65



FEATURES

Depth control adjustment.
High capacity rear loading magazine.
Rubber grip provide comfortable feel.

APPLICATIONS

Decoration
Light frame
Door & Window

Boards in furniture
Hardwood flooring

SPECIFICATIONS

Dimensions (mm)	L287 x W73 x H278
Weight	1,76 kg
Operating pressure	100 - 120 psi
Magazine capacity	100 brads
Fastener diameter	1,60mm
Fastener length	25 - 63mm

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for 16 gauge straight brads

Product Code	Description	QTY
EC-BC65	ECKO 16 Gauge Air Straight Bradder	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

Wrap-Tacker® Air Stapler RD1116P



APPLICATIONS

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

SPECIFICATIONS

Dimensions (mm) L220 x W140 x H45
Weight 1 kg
Operating pressure 70 - 100 psi
Magazine capacity 100 staples
Fastener length 6 - 14mm

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for 140/A11 series staples.

Product Code	Description	QTY
EC-RD1116P	ECKO Wrap-Tacker® Air Stapler	Each
EC-XPRO	ECKO Construction Hammer Tacker (6 - 14mm)	Each
EC-LT1	ECKO H/D Staple Gun Tacker (6 - 14mm)	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

Construction Hammer Tacker XPRO



APPLICATIONS

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

SPECIFICATIONS

Dimensions (mm)	L310 x W30 x H75
Weight	1,06 kg
Fasteners length	6 - 14mm

FASTENERS

Check our fasteners catalogue for 140/A11 series staples.

H/D Staple Gun Tacker LT1



APPLICATIONS

Moisture wrap
House wrap
Roofing felt
Foam sheathing insulation
Labelling

SPECIFICATIONS

Dimensions (mm)	L250 x W30 x H150
Weight	1,07 kg
Fasteners length	6 - 14mm

FASTENERS

Check our fasteners catalogue for 140/A11 series staples.

Palm Nailer PNC1



FEATURES

Perfect for timber framing in construction site.
Ideal for driving loose nails in confined area & for nailing of metal connectors & joist hangers.
Easier & Simple to use.

SPECIFICATIONS

Dimensions (mm)	L132 x W82 x H124
Weight	1,18 kg
Operating pressure	100 - 120 psi
Magazine capacity	1 nail
Fastener diameter	2,87 - 4,10mm (standard nose) 4,88 - 7,94mm (large nose) - optional
Fastener length	32 - 178mm

APPLICATIONS

Retaining wall

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for loose nails series.

Product Code	Description	QTY
EC-PNC1	ECKO Palm Nailer	Each
EC-OIL250	ECKO Premium Pneumatic Tool Lubricant 250ml	Each

RebarMaster Cordless Rebar Tool XPOWERPLUS



FEATURES

Save up to 80% in time & labour.
 No more RSI.
 One handed operation.
 Consistent fixing performance.
 Brushless twisting motor.

SPECIFICATIONS

Dimensions (mm)	L297 x W109 x H300
Weight (incl. battery)	2,60 kg
Time per tie	0,7 second
Wraps per tie	2 or 3 wraps
Rebar size	12 - 40mm
Ties per coil	Approx. 160 ties
Ties per charge	Over 5,000 ties / 2 wraps Over 4,500 ties / 3 wraps
Charging time	90 minutes

APPLICATIONS

Foundations
 Floor heating
 Commercial buildings
 Road & Bridge
 Precast plants

MAINTENANCE

Recommended 10 drops daily. Disconnect the air hose, apply 10 drops of pneumatic oil into the nailer.

FASTENERS

Check our fasteners catalogue for rebar wire.

Product Code	Description	QTY
EC-XPOWERPLUS	ECKO RebarMaster Cordless Rebar Tool (Li-ion Battery)	Each
XP-080G	RebarMaster™ Hardened rebar wire - 0.80mm	20 coils